

# ALTEA 500 LED

astro

## GENERAL

CLASS:	CE (Class 2)
IP RATING:	IP44
BATHROOM ZONE:	Zone 2, 3
VOLTAGE:	Mains 230V
INSTALLATION ORIENTATION:	Wall mount
MAIN MATERIAL:	Metal - Zinc
DIMENSIONS:	H: 500mm W: 90mm D: 59mm
CUT OUT HOLE:	Not applicable
RECESS DEPTH:	Not applicable
FIRE RATING:	Not applicable
CABLE LENGTH:	Not applicable
GROSS WEIGHT:	1.86Kg

## LAMP

LIGHT SOURCE:	LED STRIP
MAXIMUM WATTAGE:	20.3W
LAMP INCLUDED:	Yes (Integral)
MAXIMUM LAMP LENGTH:	Not Applicable
LUMINOUS FLUX:	858 lm
COLOUR TEMP:	3000K
CRI:	80
R9:	7.0
MACADAM ELLIPSE:	+/-100K
TILT ADJUSTABLE ANGLE:	Not applicable
ROTATION ADJUSTABLE ANGLE:	Not applicable
AVERAGE LIFESPAN:	50,000hrs
L70:	Not applicable
BEAM ANGLE:	Not applicable

## ELECTRICAL


SWITCHED:	No
DIMMABLE:	No
DIMMING METHOD:	Not applicable
DRIVER INCLUDED:	Yes (Integral)
DRIVER OUTPUT CURRENT:	Not applicable
DRIVER OUTPUT VOLTAGE:	12V
SUPPLY FREQUENCY:	47/63Hz
DRIVER/BALLAST VOLTAGE:	90-264V
DRIVER AVERAGE LIFESPAN:	20,000hrs
EFFICACY:	42.27lm/W

## ADDITIONAL INFORMATION:

SHADE INCLUDED:	-
SHADE/DIFFUSER MATERIAL:	Polycarbonate
SHADE/DIFFUSER FINISH	Natural
F MARK:	Suitable for mounting on flammable materials



CODE 8015  
SKU 1133006  
FINISH POLISHED CHROME



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes

Veuillez noter que certaines dimensions peuvent varier légèrement en raison des tolérances de fabrication, y compris l'entrée de câble et les trous de fixation.

Bitte beachten Sie, dass die Maße Fertigungstoleranzen unterliegen und daher in geringem Umfang von der angegebenen Größe abweichen können. Dies gilt auch für Kabeleingänge und Befestigungslöcher.

Si prega notare che possono esserci piccole variazioni in alcune dimensioni dovute alle tolleranze di produzione, queste includono l'ingresso del cavo e i fori di fissaggio.