FUSE UNSWITCHED 7859

SKU 1215025



PRODUCT SPECIFICATION

GENERAL

FINISH: Matt Nickel CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Aluminium **GROSS WEIGHT:** 1.85(kg) H: 180mm W: 75mm D: 62mm **DIMENSIONS:** CLASS: CE (Class II) INSTALLATION ORIENTATION: Wall Mount - Horizontal/Vertical IP RATING: IP20 Not Applicable **CUT OUT HOLE: BATHROOM ZONE:** Zone 3

RECESS DEPTH: 62mm VOLTAGE: Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: High-Power LED MACADAM ELIPSE: 3-Step

MAXIMUM WATTAGE: UGR: 3W Not Applicable MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** 16 (Degrees)

LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: 90 (Degrees) **LUMINOUS FLUX:** 106 (lm) ROTATION ADJUSTMENT ANGLE: 330 (Degrees) **COLOUR TEMP:** AVERAGE LIFESPAN: 3000 (K) 54,000 (Hrs) CRI: 80 L70: To Be Advised

R9: 10.8

ELECTRICAL

SWITCHED: SUPPLY FREQUENCY: No 50/60 (Hz) DIMMABLE: No DRIVER/BALLAST VOLTAGE: 220-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 60,000 (Hrs) **DRIVER OUTPUT CURRENT:** 700 (mA) EFFICACY: 24.95 (lm/W)

DRIVER OUTPUT VOLTAGE: DRIVER INCLUDED? Not Applicable Yes (Integral)


ADDITIONAL INFORMATION




BOX QUANTITY X12


Œ


TOP



FRONT SIDE BACK







T: +44 (0) 1279 427001 F: +44 (0) 1279 427002 sales@astrolighting.com www.astrolighting.com