## astro



## SPECIFICATION

DRIVER CURRENT350mADRIVER VOLTAGEN/ADIMMABLE1-10VELECTRICAL CLASSCLASS 2SUPPLY VOLTAGE220-240V ACSUPPLY FREQUENCY50/60HzPOWER FACTOR0.55MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE3.0.0V DCMAX. OUTPUT POWER1.05WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE200mmLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEPMODEL NUMBERLPVC11A1C	ТҮРЕ	Constant current
DIMMABLE1-10VELECTRICAL CLASSCLASS 2SUPPLY VOLTAGE220-240V ACSUPPLY FREQUENCY50/60HzPOWER FACTOR0.55MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE30.0V DCMIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	DRIVER CURRENT	350mA
ELECTRICAL CLASSCLASS 2SUPPLY VOLTAGE220-240V ACSUPPLY FREQUENCY50/60HzPOWER FACTOR0.55MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE30.0V DCMAX. OUTPUT POWER1.05WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCEHEP	DRIVER VOLTAGE	N/A
SUPPLY VOLTAGE220-240V ACSUPPLY FREQUENCY50/60HzPOWER FACTOR0.55MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE30.0V DCMIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCEHEP	DIMMABLE	1-10V
SUPPLY FREQUENCY50/60HzPOWER FACTOR0.55MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE30.0V DCMIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	ELECTRICAL CLASS	CLASS 2
POWER FACTOR0.55MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE30.0V DCMIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	SUPPLY VOLTAGE	220-240V AC
MIN. OUTPUT VOLTAGE3.0V DCMAX. OUTPUT VOLTAGE30.0V DCMIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	SUPPLY FREQUENCY	50/60Hz
MAX. OUTPUT VOLTAGE30.0V DCMIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	POWER FACTOR	0.55
MIN. OUTPUT POWER1.05WMAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	MIN. OUTPUT VOLTAGE	3.0V DC
MAX. OUTPUT POWER10.5WINRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	MAX. OUTPUT VOLTAGE	30.0V DC
INRUSH CURRENT58.0AIP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	MIN. OUTPUT POWER	1.05W
IP RATINGIP20WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	MAX. OUTPUT POWER	10.5W
WORKING TEMPERATURE-20°C - +50°CCONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	INRUSH CURRENT	58.0A
CONNECTION TYPEScrew terminalsLENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	IP RATING	IP20
LENGTH200mmWIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	WORKING TEMPERATURE	-20°C - +50°C
WIDTH42.40mmHEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	CONNECTION TYPE	Screw terminals
HEIGHT38.80mmMIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	LENGTH	200mm
MIN. CIRCULAR APERTURE57mm/2-1/4"MAX. LED DISTANCENot StatedMANUFACTURERHEP	WIDTH	42.40mm
MAX. LED DISTANCENot StatedMANUFACTURERHEP	HEIGHT	38.80mm
MANUFACTURER HEP	MIN. CIRCULAR APERTURE	57mm/2-1/4"
	MAX. LED DISTANCE	Not Stated
MODEL NUMBER LPVC11A1C	MANUFACTURER	HEP
	MODEL NUMBER	LPVC11A1C

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.