

LED DRIVER 350/500/700mA 15/20W

CODE 6008058 (2126)

astro



SPECIFICATION

TYPE	Constant current
DRIVER CURRENT	350/500/700mA
DRIVER VOLTAGE	N/A
DIMMABLE	1-10V DIMMING
ELECTRICAL CLASS	CLASS 2
SUPPLY VOLTAGE	110-240V AC
SUPPLY FREQUENCY	50/60Hz
POWER FACTOR	0.95
MIN. OUTPUT VOLTAGE	2.0V DC
MAX. OUTPUT VOLTAGE	43.0V/40.0/29.0V DC
MIN. OUTPUT POWER	0.7/1.0/1.4W
MAX. OUTPUT POWER	15.05/20.0/20.3W
INRUSH CURRENT	5A for 50 μ S
IP RATING	IP20
WORKING TEMPERATURE	-25°C - +50°C
CONNECTION TYPE	Push Connection
LENGTH	108mm
WIDTH	52mm
HEIGHT	22mm
MIN. CIRCULAR APERTURE	57mm/2-1/4"
MAX. LED DISTANCE	5m 23AWG
MANUFACTURER	TCI
MODEL NUMBER	DC MINI JOLLY

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.